

Data Sheet ABS FF

rev. 1.0 24/01/2024

SUGGESTED PRINT SETS (1)			
Suggested print sets	unit	value	test method
extruder temp	C°	235-250	internal
plate temp	C°	90	internal
min. nozzle diameter	mm.	0,2	internal
fan	%	0-70	internal
Max print speed	mm/sec.	510	internal
PROPERTY			
Physical			
Specific gravity	g/cm3	1.05	ISO 1183
Mechanical at 23°C / 50% rh			
Flexural modulus	MPa	2400	ISO 527
Tensile stress	MPa	45	ISO 527
Charpy impact (23°C)	kJ/m²	23	ISO 179
Charpy impact (-30°C)	kJ/m²	10	ISO 179
Thermal			
H.D.T. B	°C	90	ISO 75-2
H.D.T.A	°C	80	ISO 75-2
Vicat softening temp.	°C	100	ISO 306

Disclaimer

The above information is provide in good fact .Treedfilaments is not responsable for any processing which may occur to product finished articles , packaging materials and other .

Further Treedfilaments makes no warranty or representation of any kind regarding the information given or the product described and expressly disclaims all implied warranties , representations and conditions , including without limitation all warranties and conditions of quality , merchantability and suitability or fitness for particular purpose .



Data Sheet ABS ZX

rev. 1.0 24/01/2024

ADDITIONAL INFORMATIONS

In General filaments made with ABS FF can be processed on conventional 3D printer using FDM / FFF technology.

ABS FF is a special ABS developed for 3D printing and to obtain best results we recommend pre drying the filaments at 70° for 2 h. Increase drying time for spools up 1 kg.

Don't leave the filament stopped inside the nozzle more than 20 min. If that down the temperature under 200°, better stop the thermal control.

(1) Suggested print set merely represent a recommendation for general use . Every printer necessity a specific set , nozzle temp, bed temp, etc .

Disclaimer

The above information is provide in good fact .Treedfilaments is not responsable for any processing which may occur to product finished articles , packaging materials and other .

Further Treedfilaments makes no warranty or representation of any kind regarding the information given or the product described and expressly disclaims all implied warranties , representations and conditions , including without limitation all warranties and conditions of quality , merchantability and suitability or fitness for particular purpose .